



THERMAL STORAGE MESH 6W FOR INTERIOR EMBEDDED CONCRETE



240 Volts							
Model	Length		Spacing (ft ²)	Power Output			
	ft.	m.	6" 11 W	Watt	Amp	Ohms	
6MTS-240V-015	7,5	2,3	15,0	165	0,7	349,1	
6MTS-240V-020	10,0	3,0	20,0	220	0,9	261,8	
6MTS-240V-025	12,5	3,8	25,0	275	1,1	209,5	
6MTS-240V-031	15,5	4,7	31,0	341	1,4	168,9	
6MTS-240V-038	19,0	5,8	38,0	418	1,7	137,8	
6MTS-240V-046	23,0	7,0	46,0	506	2,1	113,8	
6MTS-240V-055	27,5	8,4	55,0	605	2,5	95,2	
6MTS-240V-065	32,5	9,9	65,0	715	3,0	80,6	
6MTS-240V-076	38,0	11,6	76,0	836	3,5	68,9	
6MTS-240V-088	44,0	13,4	88,0	968	4,0	59,5	
6MTS-240V-101	50,5	15,4	101,0	1111	4,6	51,8	
6MTS-240V-115	57,5	17,5	115,0	1265	5,3	45,5	
6MTS-240V-130	65,0	19,8	130,0	1430	6,0	40,3	
6MTS-240V-146	73,0	22,3	146,0	1606	6,7	35,9	
6MTS-240V-161	80,5	24,5	161,0	1771	7,4	32,5	
6MTS-240V-177	88,5	27,0	177,0	1947	8,1	29,6	
6MTS-240V-192	96,0	29,3	192,0	2112	8,8	27,3	
6MTS-240V-207	103,5	31,5	207,0	2277	9,5	25,3	
6MTS-240V-222	111,0	33,8	222,0	2442	10,2	23,6	
6MTS-240V-237	118,5	36,1	237,0	2607	10,9	22,1	
6MTS-240V-252	126,0	38,4	252,0	2772	11,6	20,8	
6MTS-240V-267	133,5	40,7	267,0	2937	12,2	19,6	
6MTS-240V-282	141,0	43,0	282,0	3102	12,9	18,6	
6MTS-240V-297	148,5	45,3	297,0	3267	13,6	17,6	
6MTS-240V-312	156,0	47,5	312,0	3432	14,3	16,8	
6MTS-240V-325	162,5	49,5	325,0	3575	14,9	16,1	